

# 3D Stereolithography Printers

The gold standard in Stereolithography (SLA) 3D printing



Projet® 6000



Projet® 7000



ProX® 800



ProX® 950

Max Build Volume (xyz) <sup>1</sup>	Flexible build volume options with interchangeable material delivery modules (MDM)			
Full	10 x 10 x 10 in (250 x 250 x 250 mm) 10.6 U.S. gal (40 l)	15 x 15 x 10 in (380 x 380 x 250 mm) 22.2 U.S. gal (84 l)	25.6 x 29.5 x 21.65 in (650 x 750 x 550 mm); 109.3 U.S. gal (414 l)	59 x 30 x 22 in (1500 x 750 x 550 mm); 247 U.S. gal (935 l)
Half	10 x 10 x 5 in (250 x 250 x 125 mm) 5.8 U.S. gal (22 l)	N/A	25.6 x 29.5 x 10.8 in (650 x 750 x 275 mm); 71.9 U.S. gal (272 l)	N/A
Short	10 x 10 x 2 in (250 x 250 x 50 mm) 6.3 U.S. gal (24 l)	15 x 15 x 2 in (380 x 380 x 50 mm) 8.5 U.S. gal (32 l)	25.6 x 29.5 x 1.97 in (650 x 750 x 50 mm); 25.09 U.S. gal (95 l)	N/A
<b>Max Part Weight</b>	21.1 lb (9.6 kg)	47.6 lb (21.6 kg)	165 lbs (75 kg)	330 lbs (150 kg)
<b>Max Resolution</b>	4000 DPI <sup>2</sup>	4000 DPI <sup>2</sup>	4000 DPI <sup>2</sup>	4000 DPI <sup>2</sup>
<b>Intelligent Scanning Strategy</b>	Automated in build dual mode speeds: Fine point scanning for small feature and external surfaces, broader scanning for larger features and internal surfaces.			
Fine Feature/Outer Surface Scanning	Down to 75 µm (0.003 in)	Down to 75 µm (0.003 in)	125 µm (0.005 in)	125 µm (0.005 in)
Larger Feature/Internal Surface Scanning	750 µm (0.030 in)	750 µm (0.030 in)	750 µm (0.030 in)	750 µm (0.030 in)
<b>Accuracy</b>	0.001-0.002 inch per inch (0.025-0.05 mm per 25.4 mm) of part dimension Accuracy may vary depending on build parameters, part geometry and size, part orientation and post-processing methods			
<b>Materials</b>	Builds with broadest range of 3D printing materials with exceptional mechanical properties. See backpage for choice of available materials and <a href="http://www.3dsystems.com">www.3dsystems.com</a> for all available materials.			
<b>Material Packaging</b>	2 l click in cartridges for hands-free, drip-free automated refill process.		10 kg click in cartridges for hands-free, drip-free automated refill process.	
<b>Electrical Requirements</b>	100-240 VAC, 50/60 Hz, single-phase, 750 W	100-240 VAC, 50/60 Hz, single-phase, 750 W	200 - 240 VAC 50/60 Hz, single-phase, 30 amps	200 - 240 VAC 50/60 Hz, single-phase, 50 amps
<b>Dimensions (WxDxH)</b>				
3D Printer Crated	66 x 35 x 79 in (1676 x 889 x 2006 mm)	73.5 x 38.5 x 81.5 in (1860 x 982 x 2070 mm)	75 x 64 x 98 in (190 x 163 x 248 cm)	95 x 68 x 100 in (242 x 173 x 254 cm)
3D Printer Uncrated	31 x 29 x 72 in (787 x 737 x 1829 mm)	39.0 x 34.0 x 72 in (984 x 854 x 1829 mm)	50 x 63 x 89 in (137 x 160 x 226 cm)	87 x 63 x 89 in (220 x 160 x 226 cm)
<b>Weight (not incl. MDM)</b>				
3D Printer Crated	600 lb (272 kg)	800 lb (363 kg)	2500 lbs (1134 kg)	4300 lbs (1951 kg)
3D Printer Uncrated	400 lb (181 kg)	600 lb (272 kg)	2000 lbs (907 kg)	3800 lbs (1724 kg)
<b>Print3DPro and 3DManage™ Software</b>	Easy build job set-up, submission and job queue management Automatic part placement and build optimization tools Part nesting capability Extensive part editing tools Automatic support generation Job statistics reporting			
<b>MPAuto Software</b>	Software development tool for 3DManage software. MPAuto Software enables 3D Printing preparation process integration into other digital production software.			
<b>Network Compatibility</b>	Network ready with 10/100 Ethernet interface 4MB		Ethernet, IEEE 802.3 using TCP/IP and NFS	
<b>3D Manage Hardware Recommendation</b>	I5, 2.3 GHz with 8 GB RAM (Open GL support 1GB video RAM)		I5, 2.3 GHz with 8 GB RAM (Open GL support 1GB video RAM)	
<b>Software Operating System</b>	Windows® XP Professional, Windows® Vista, Windows® 7		Windows® 7 and newer	
<b>Input Data File Formats Supported</b>	STL and SLC		STL and SLC	STL and SLC
<b>Operating Temperature Range*</b>	64-82 °F (18-28 °C)		68-79 °F (20-26 °C)	68-79 °F (20-26 °C)
<b>Noise</b>	< 65 dBa estimated		Not to exceed 70 dBA	Not to exceed 70 dBA
<b>Interchangeable Material Deliverable Modules (MDMs) with integrated elevator and removable applicator</b>	Additional MDM (3 size's)		Additional MDM (3 size's)	Additional MDM (1 size)
<b>Accessories</b>	UV Curing Units Parts Washer Right Height Table Projet® Cart Station		Manual offload cart ProCure™ 750 or 1500 UV Finisher	Manual offload cart ProCure™ 750 or 1500 UV Finisher

<sup>1</sup> Maximum part size is dependent on geometry, among other factors.

<sup>2</sup> Equivalent DPI based on laser spot location resolution of 0.00635 mm in 3DS testing.

# Visijet® Materials for SLA Printing on ProJet 6000 & 7000

The wide range of Visijet SL engineered materials offers the toughest and the highest quality parts to meet a broad range of commercial and production applications.



Visijet SL Black




Visijet SL Jewel



Visijet SL Tough (frame) and Visijet SL Clear (lenses)



Visijet e-Stone



Visijet SL Clear



Visijet SL Impact

Materials for ProJet 6000/7000 Printers <sup>1</sup>	Viscosity (cps) (@ 30 °C)	Flexural Modulus (MPa) ASTM D 790	Flexural Strength (MPa) ASTM D 790	Tensile Modulus (MPa) ASTM D 638	Tensile Strength (MPa) ASTM D 638	Elongation at Break ASTM D 638	Impact Strength (J/m) ASTM D 256	Heat Deflection Temp (°C) ASTM D 648
<b>Polypropylene-Like Class</b>								@ 1.82 MPa
Visijet SL Flex	180-280	1420	57	1620	38	16%	22	53 °C
<b>Tough/Durable Class</b>								
Visijet SL Tough	180-250	1850	62	1890	41	18%	44	54 °C
Visijet SL Impact	680-780	2390	74	2626	48	14%	65	42 °C
<b>ABS-Like Class</b>								
Visijet SL Black	180-260	2350	76	2150	45	5%	47	51 °C
<b>Clear/Castable Class</b>								
Visijet SL Clear <sup>2</sup>	200-300	2330	83	2560	52	6%	46	50 °C
<b>High Temp Class</b>								
Visijet SL HiTemp	100-160	3080	112	3390	66	6%	26	57/110 °C
<b>Jewelry &amp; Dental Class</b>								
Visijet SL Jewel	130 - 200	1824	61	1910	40	12%	45	32 °C
Visijet e-Stone™	170-270	1550	57	1630	38	17%	22	53 °C
<b>Medical Class</b>								
Visijet SL Clear <sup>2</sup>	200-300	2330	83	2560	52	6%	46	50 °C

<sup>1</sup> Not all materials will build in all build modes and on every printer model. Check with your local sales representative to verify the combination you are looking for is available.

<sup>2</sup> USP Class VI capable

[www.3dsystems.com](http://www.3dsystems.com)

**KISTERS**

Telefon 02408/9385-514 | [vertrieb@projet-3D-drucker.de](mailto:vertrieb@projet-3D-drucker.de)

[www.projet-3D-drucker.de](http://www.projet-3D-drucker.de)

Aachen | Cottbus | Duisburg | Erlangen | Kiel | München | Oldenburg